



Amazing fire presentation, efficient operation and quality construction come together to provide long-lasting warmth and unsurpassed beauty in a traditional hearth setting.

LENNOX

HEARTH PRODUCTS
Innovation never felt so good.™



HC-36 shown with optional brass louvers and brass bi-fold doors.

MERIT™ SERIES

With openings of 36" and 42", the HC and RD Merit™ Series wood-burning fireplaces present outstanding hearth views and remarkable fire presentations. Featuring high-efficiency operation and durable components, these fireplaces are built to last. And the appearance of a custom masonry-built fireplace, featuring a clean and attractive design, is sure to add a touch of majesty to any home.




HC-42




RD-36

HC-36/42 & RD-36/42 DIMENSIONS


Front View



Right Side View



Top View



	RD/HC-36	RD/HC-42
A	44-1/4"	46-5/16"
B	36-5/16"	38-7/16"
C	20-3/16"	22-5/16"
D	36"	41"
E	9"	8-3/8"
F	21-5/16"	23-1/2"
G	17-7/16"	17-5/16"
H	10-1/8"	10"
I	41-3/4"	46-3/4"
J	13-1/4"	15"
K	28-1/8"	31-9/16"

STANDARD FEATURES

Large 36" and extra-large 42" firebox openings offer remarkable viewing areas for enchanting fires

Uses Security Chimneys™ FTF8 8" chimney system for added convenience and easy installation

Durable powder-coat finish creates scratch-resistant surfaces and carefree handling

Hidden screen pockets retract when not in use for a clean and elegant look

Heavy-duty steel grate provides stability for uncomplicated fuel loading

Factory installed outside air mechanism provides easy access and improves performance

OPTIONAL ACCESSORIES

Bi-fold glass doors in black, brass and brushed stainless finishes (Twin-pane glass doors in brass only)


Standard or herringbone brick patterned liner

Brass or brushed stainless louver finishes (HC models only)


Blower kit (HC models only)

INSIDE HEARTH DIMENSIONS

HC/RD-36




HC/RD-42




FRAMING DIMENSIONS

Model	Width	Height	Depth
HC-36	43"	44-1/2"	21-3/4"
HC-42	48"	46-1/2"	24"
RD-36	43"	44-1/2"	21-3/4"
RD-42	48"	46-1/2"	24"



Standard brick liner



Herringbone brick liner

On the cover: RD-42 shown with optional brass bi-fold glass doors and herringbone brick patterned liner.

LENNOX

HEARTH PRODUCTS
Innovation never felt so good.™

© Lennox Industries Inc. 2007

Visit us at www.lennox.com, or contact us at 1-800-9-LENNOX.

IMPORTANT NOTES:

As with any heating appliance, fireplace or stove, this appliance is extremely hot during operation. Read and understand all operating instructions before using this appliance. For further information, consult your dealer.

Actual performance may vary depending upon home design and insulation, ceiling heights, climate, condition and type of wood used, appliance location, burn rate, accessories chosen, chimney installation and how the appliance is operated.

Diagrams, illustrations and photographs are not to scale - consult installation instructions. Product designs, materials, dimensions, specifications, colors and prices are subject to change or discontinuance without notice.

Built to UL127/ULCS610 standard. Agency report numbers, local approvals, including WA State and NYC vary by model. Refer to specific installation instructions or our website for details.

