

Woodburning Systems Accessories & Non-Stock Fireboxes

Dimensions



ICON Series I60 & I80 Woodburning Fireplaces

SL1100 Series Pipe:
 11" diameter inner pipe;
 13" diameter outer pipe;
 Clearance to outer pipe: 2"

| Model | Width | Depth | Front Header Height | Back Header Height ① |
|-------|---------|---------|---------------------|----------------------|
| I60 | 45 1/2" | 28" | 49 3/4" | 59 1/4" |
| I80 | 51 1/2" | 28 1/2" | 49 5/8" | 59 1/4" |

| Model | A | B | C |
|-------|-----|---------|---------|
| I60 | 36" | 44 1/2" | 28 5/8" |
| I80 | 42" | 50 1/2" | 34 1/2" |

| Model | Depth |
|-------|---------|
| I60 | 23 3/4" |
| I80 | 24 1/2" |

① This dimension represents the distance from the base of the unit to the top of the back standoff.
 For best results, do not construct the framing until the unit is in place.

ICON Series I100 Woodburning Fireplaces

Firebox depth: 25 1/2"

Specifications

| Height | | Header Height | | Front Width | | Back Width | | Depth | | Glass Size |
|---------|---------|---------------|---------|-------------|---------|------------|---------|---------|---------|------------|
| Actual | Framing | Actual | Framing | Actual | Framing | Actual | Framing | Actual | Framing | |
| 70 1/2" | 71" | 60 1/4" | 61" | 60 5/8" | 61 5/8" | 41 5/8" | 61 5/8" | 29 1/2" | 30 3/8" | 50" x 33" |

Note: Fireplace header cannot be positioned until after the fireplace assembly is in place.
 61" header height. Use only noncombustible material below the top standoffs.

For best results, do not construct the framing until the unit is in place.